



Pre-Engineered Heavy-duty design

Bolted construction requires no field welding

Slip-resistant design with built-in toe boards

Built-to-last, constructed with galvanized G140 U.S. Prime Steel






Ε

**Silver Grip® Grating**: Features a perforated and rugged design with our proprietary slip and water drainage decking floor.



Secured Handrails





**Angled Tube Supports:** Provide quality support and strength.



Walkway Widths: Available in 24", 30", and 36" wide walkways.



**Modular Standard Sections:** Available in 5', 10', 15', or 20' modular sections.



**Structural Truss** Available in 18" and 30" tall.




Drive Service Platform: Optional for conveying systems that have large drives.

All our Silver Span<sup>®</sup> Support Systems features a frame made of galvanized G140 U.S. prime steel base assemblies, ensuring a longer lifespan while making it maintenance-free and safer for your team. Additionally, our bolted construction eliminates the need for welding, making it easier to install while providing a versatile solution for your unique conveyor needs.

## **SILVER SPAN** CONVEYOR SUPPORT SYSTEM

Model	Α	в	с	D
24" Walkway	22"	-	28.5"	18"
30" Walkway	28"	-	34.5"	18"
36" Walkway	34"	-	40.5"	18"
242418	22"	21"	52.5"	18"
243618	22"	33"	64.5"	18"
244818	22"	45"	76.25"	18"
24" Walkway	22"	-	28.5"	30.
30" Walkway	28"	-	34.5"	30"
36" Walkway	34"	-	40.5"	30"
242430	22"	21"	52.5"	30"
243630	22"	33"	64.5"	30"
244830	22"	45"	76.25"	30"



Typical Conveyor Loading (Pounds per foot)												
Silver Span <sup>®</sup> Model	No Conveyor Man Walkway	40	70	90	110	130	150	190	210	240	270	300
18" Truss	Unsupported Distance of Span between Supports											
Without Cable Truss	60 ft.	60 ft.	55 ft.	50 ft.	50 ft.	45 ft.	45 ft.	40 ft.	35 ft.	33 ft.	30 ft.	XXX
Min. Lower Chord Angle	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	3/16"	3/16"	1/4"	1/4"	XXX
With Single Cable Truss	80 ft.	75 ft.	70 ft.	65 ft.	60 ft.	55 ft.	50 ft.	45 ft.	40 ft.	38 ft.	XXX	XXX
Min. Lower Chord Angle	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	3/16"	3/16"	3/16"	1⁄4"	XXX	XXX
With Double Cable Truss	100 ft.	90 ft.	85 ft.	80 ft.	75 ft.	70 ft.	65 ft.	50 ft.	50 ft.	47 ft.	42 ft.	XXX
Min. Lower Chord Angle	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"	1/4"	1/4"	1/4"	1/4"	1/4"	XXX
30" Truss												
Without Cable Truss	80 ft.	75 ft.	70 ft.	65 ft.	60 ft.	55 ft.	50 ft.	45 ft.	40 ft.	38 ft.	35 ft.	30 ft.
Min. Lower Chord Angle	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	3/16"	3/16"	1/4"	1⁄4"	5/16"	5/16"
With Single Cable Truss	100 ft.	90 ft.	85 ft.	80 ft.	75 ft.	70 ft.	65 ft.	60 ft.	50 ft.	46 ft.	XXX	XXX
Min. Lower Chord Angle	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	3/16"	3/16"	3/16"	1⁄4"	XXX	XXX
With Double Cable Truss	120 ft.	100 ft.	100 ft.	90 ft.	90 ft.	80 ft.	75 ft.	70 ft.	60 ft.	56 ft.	50 ft.	46 ft.
Min. Lower Chord Angle	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	10 ga.	3/16"	3/16"	1/4"	1⁄4"	5/16"	5/16"
Corresponding Sweet Conveyor*	-	- - 9" RB 9" UT	- 1017 IFV 12" RB 12" UT	1017 HFV 1017 IFV 14" RB 14" UT	1417 HFV 1817 IFV 16" RB 16" UT	1817 HFV 2017 IFV - 18" UT	2017 HFV - - -	- - -	- - -	1826 HFV - - -	2426 HFV - - -	3026 HFV - - -

Key \* HFV IFV

Sweet® Conveyors Handling Grain @ 48 PCF Sweet® Flite-Veyor® Horizontal Flat Bottom Drag Conveyors Sweet® Flite-Veyor® Incline Flat Bottom Drag Conveyors Note: Dimensions are for reference only and may be subject to change

Sweet® Flite-Veyor® Round Bottom Drag Conveyors CEMA Standard U-Trough Conveyors


Do not use

RB

UT XXX



2000 East Leffel Lane Springfield, Ohio, 45505, USA



sweetmfg.com @

## MADE IN AMERICA

ONE OF THE COUNTLESS REASONS WHY IT'S SWEET®.

An extraordinary service experience.

Innovative product solutions made with all galvanized construction with USA prime steel and premium components.



